

Bacula

• Bacul PARSEC_CAP_UNSAFE_SETXATTR



:

- Astra Linux Special Edition .10015-01 (1.6)
- Astra Linux Special Edition .10015-01 (1.5)
- Astra Linux Special Edition .10015-16 . 1

Bacul PARSEC_CAP_UNSAFE_SETXATTR



Astra Linux Special Edition .10015-01 (1.6) PARSEC_CAP_UNSAFE_SETXATTR FileDaemon " ", /parsecfs/unsecure_setxattr .

, Bacula (Bacula - FileDaemon) (,) , - PARSEC_CAP_UNSAFE_SETXATTR (0x1000), -. , .
execaps (. ,).
/ bacula , , , PARSEC_CAP_UNSAFE_SETXATTR , (), /etc/init.d/bacula-fd :



start-stop-daemon -c "\$DAEMONUSER" --start



execaps -c 0x1000 -- start-stop-daemon -c "\$DAEMONUSER" --start

, :

```
sudo sed -i -e 's/start-stop-daemon -c "$DAEMONUSER" --start/execaps -c 0x1000 -- start-stop-daemon -c "$DAEMONUSER" --start/g' /etc/init.d/bacula-fd
```



:

```
sudo service bacula-fd restart
```



PARSEC_CAP_UNSAFE_SETXATTR , , /parsecfs/unsecure_setxattr.

, , , SSH, :

```
echo 1 | sudo tee /parsecfs/unsecure_setxattr
```

, , /parsecfs/unsecure_setxattr:

```
echo 0 | sudo tee /parsecfs/unsecure_setxattr
```

, Bacula. /etc/bacula/scripts/before_restore /etc/bacula/scripts/after_restore. , :

```
sudo touch /etc/bacula/scripts/before_restore /etc/bacula/scripts
/after_restore
sudo chmod +x /etc/bacula/scripts/before_restore /etc/bacula/scripts
/after_restore
```

:

/etc/bacula/scripts/before_restore

```
#!/bin/bash
echo 1 | sudo tee /parsecfs/unsecure_setxattr
```

/etc/bacula/scripts/after_restore

```
#!/bin/bash
echo 0 | sudo tee /parsecfs/unsecure_setxattr
```

/etc/bacula/job.d/restore-dir-fd.conf, ClientRunBeforeJob ClientRunAfterJob ():

```
Job {
#
Name = "RestoreFiles"
# (backup, restore ..)
Type = Restore
#
Client=dir-fd
#
FileSet="Full Set"
#
ClientRunBeforeJob = "/etc/bacula/scripts/before_restore"
#
ClientRunAfterJob = "/etc/bacula/scripts/after_restore"
#
Storage = stor-sd
#
Pool = File
#
Messages = Standard
#
Where = /restore
}
```