Bacula

- Bacul PARSEC_CAP_UNSAFE_SETXATTR

:

- Astra Linux Special Edition .10015-01 (1.6)
- Astra Linux Special Edition .10015-01 (1.5)
- Astra Linux Special Edition .10015-16 . 1

Bacul PARSEC_CAP_UNSAFE_SETXATTR

Astra Linux Special Edition .10015-01 (1.6) PARSEC_CAP_UNSAFE_SETXATTR FileDaemon " ", /parsecfs /unsecure_setxattr .

, Bacula (Bacula - FileDaemon) (,) , - PARSEC_CAP_UNSAFE_SETXATTR (0x1000), -. , .

execaps (. ,).

/ bacula , , , PARSEC_CAP_UNSAFE_SETXATTR , ( ), /etc/init.d/bacula-fd :

start-stop-daemon -c "$DAEMONUSER" --start

execaps -c 0x1000 -- start-stop-daemon -c "$DAEMONUSER" --start

, :

```
sudo sed -i -e 's/start-stop-daemon -c "$DAEMONUSER" --start/execaps -c 0x1000 -- start-stop-daemon -c "$DAEMONUSER" --start/g' /etc/init.d/bacula-fd
```

:

```
sudo service bacula-fd restart
```

PARSEC_CAP_UNSAFE_SETXATTR , , /parsecfs/unsecure_setxattr.

, , , , SSH, :

```
echo 1 | sudo tee /parsecfs/unsecure_setxattr
```

, , /parsecfs/unsecure_setxattr:

```
echo 0 | sudo tee /parsecfs/unsecure_setxattr
```

, Bacula. /etc/bacula/scripts/before_restore /etc/bacula/scripts/after_restore. , :

```
sudo touch /etc/bacula/scripts/before_restore /etc/bacula/scripts
/after_restore
sudo chmod +x /etc/bacula/scripts/before_restore /etc/bacula/scripts
/after_restore
```

:

/etc/bacula/scripts/before_restore

```
#!/bin/bash
echo 1 | sudo tee /parsecfs/unsecure_setxattr
```

/etc/bacula/scripts/after_restore

```
#!/bin/bash
echo 0 | sudo tee /parsecfs/unsecure_setxattr
```

/etc/bacula/job.d/restore-dir-fd.conf, ClientRunBeforeJob ClientRunAfterJob ( ):

```
 Job {
    #
    Name = "RestoreFiles"
    #   (backup, restore  ..)
    Type = Restore
    #
    Client=dir-fd
    #
    FileSet="Full Set"
    #
    ClientRunBeforeJob = "/etc/bacula/scripts/before_restore"
    #
    ClientRunAfterJob = "/etc/bacula/scripts/after_restore"
    #
    Storage = stor-sd
    #
    Pool = File
    #
    Messages = Standard
    #
    Where = /restore
}
```