

CIFS (samba DFS)

-
- samba
-
- samba
 - [homes] -
- - samba
 - CIFS/Samba
 - pam_mount
 - pam_mount
 - luserconf
- DFS
- -



:

- Astra Linux Special Edition .10015-01 (1.7)
- Astra Linux Special Edition .10015-10 ()
- Astra Linux Special Edition .10015-17
- Astra Linux Special Edition .10015-37 (7.7)
- Astra Linux Special Edition .10015-03 (7.6)
- Astra Linux Special Edition .10152-02 (4.7)
- Astra Linux Special Edition .10015-01 (1.6)
- Astra Linux Special Edition .10015-16 . 1
- Astra Linux Special Edition .10015-16 . 2
- Astra Linux Special Edition .10265-01 (8.1)
- Astra Linux Common Edition 2.12 ()

∴ [FreeIPA](#)



Astra Linux Special Edition , samba, :

1. Samba:

```
use socket MAC label = YES
```

(samba samba) ∴

```
sudo net conf setparm global "use socket MAC label" "Yes"
```

2. Astra Linux Special Edition x.7 (SMB/CIFS)



Astra Linux Special Edition x.7 .

sec=krb5i,vers=1.0, server signing = required homes. :

a. ;

b. , samba [global]:

```
server max protocol = NT1
server signing = required
```

(samba samba) ∴

```
sudo net conf setparm global "server max protocol" "NT1"
sudo net conf setparm global "server signing" "required"
```

/etc/samba/smb.conf, ;

3. , (), :

```
sudo smbcontrol all reload-config
```

- - Samba. FreeIPA , .. samba, FreeIPA (--setup-adtrust). FreeIPA samba [Samba + FreeIPA](#) [Samba Kerberos](#).
ipa0.ipadomain.ru.
- -. , FreeIPA.

samba

samba [Samba](#)

,
:
:

```
sudo mkdir /share1
```

, Astra Linux Special Edition, :

```
sudo mkdir -p /share1/{zero,dsp,secret,topsecret}
```

,
:

```
sudo chmod 777 /share1 -R
```

"4. " " . 1.10015-01 97 01-1"():

```
sudo pdpl-file 3:0:-1:ccnr /share1/
sudo pdpl-file 1:0:0 /share1/dsp
sudo pdpl-file 2:0:0 /share1/secret
sudo pdpl-file 3:0:0 /share1/topsecret
```

samba

/etc/samba/smb.conf :

/etc/samba/smb.conf

```
[global]
#
workgroup = WORKGROUP
# netbios
disable netbios = no
# , ,
map to guest = Bad User

[share1]
comment = For all doc's
#
guest ok = yes
path = /share1
read only = no
available = yes
browseable = yes
case sensitive = yes
ea support = yes
fstype = Samba
smb encrypt = auto
```



, samba- "" fly-fm NetBIOS
/etc/samba/smb.conf "disable netbios = no" ().

```
disable netbios = no
```

testparm

testparm , Samba:

```
sudo systemctl restart smbd
```

smbtree

[homes] -

[homes] - .

, .

, , :

- [global]



passdb backend = smbpasswd

- samba

```
sudo systemctl restart smbd
```

- samba:

```
smbpasswd -a username
```

[homes] /etc/samba/smb.conf :



```
[homes]
comment = Home Directories
valid users = %S
# [homes] (read only = yes).
# read only = no
read only = No
create mask = 0700
directory mask = 0700
browseable = no
guest ok = no
```

, (, smbclient username):

```
smbclient //ipa0.ipadomain.ru/username
```

, :

 smbclient //ipa0.ipadomain.ru/username -U username


```
samba , [homes].  
, , (/etc/passwd).  
, samba .  
/etc/passwd, .
```

[homes] path, , /home, .. /home/username, , /samba/users/username:


 [homes]
comment = Home Directories
valid users = %S
path = /samba/users/%S
read only = No
create mask = 0700
directory mask = 0700
browseable = no
guest ok = no

samba

(fly-fm) "", Samba NetBIOS :



NetBIOS , , "" "":



fly-fm .

CIFS/Samba

- cifs-utils:

```
sudo apt install cifs-utils
```

mount ,:

```
sudo mount.cifs /// /_ [-o ]
sudo mount -t cifs /// /_ [-o ]
```

, , , , .. /media/share1 ,:

```
sudo mkdir /media/share1
sudo chmod 777 /media/share1
sudo mount -t cifs //fileserver1.org.net/share1 /media/share1 -o user=
```

/etc/fstab sudo.
/etc/fstab , :



```
//fileserver1.org.net/share1 /media/share1 cifs user,rw,noauto,ioccharset=utf8,soft 0 0
```

```
/, user .  
mount :
```

```
mount /media/share1
```

```
man mount mount.cifs. /etc/fstab man fstab.
```

```
/etc/fstab :
```

 //fileserver1.org.net/share1 /media/share1 cifs user,rw,noauto,ioccharset=utf8,nosharesock,vers=1.0,soft 0 0



```
Kerberos      sec=krb5i sec=krb5.      Kerberos .
```



```
Kerberos      Kerberos, FreeIPA Astra Linux.  
. FreeIPA Kerberos.
```

pam_mount

```
PAM- pam_mount, libpam-mount,      - cifs-utils libpam_mount:
```

```
sudo apt install cifs-utils libpam-mount
```



```
libpam-mount  PAM-  
( /etc/pam.d/, ).  
, pam_mount  PAM- .  
,      Kerberos (. FreeIPA Astra Linux).
```

```
pam_mount /etc/security/pam_mount.conf.xml.
```

```
libpam_mount pam_mount pam- (common-auth, common-session) /etc/pam.d.
```

```
pam_mount      man pam_mount pam_mount.conf.
```

```
pam-mount      , :
```

```
/etc/security/pam_mount.conf.xml
```

```
<?xml version="1.0" encoding="utf-8" ?>  
<!DOCTYPE pam_mount SYSTEM "pam_mount.conf.xml.dtd">  
<!--  
    See pam_mount.conf(5) for a description.  
-->  
<pam_mount>  
    <!-- debug should come before everything else,  
         since this file is still processed in a single pass  
         from top-to-bottom -->  
    <debug enable="1" />  
    <!-- Volume definitions -->  
    <cifsmount>mount.cifs //%(SERVER)/%(VOLUME) %(MNTPT) -o %(OPTIONS) </cifsmount>  
    <!-- pam_mount parameters: General tunables -->  
    <!-- ,      -->  
    <volume  
        fstype="cifs"  
        server="ipa0.ipadomain.ru"  
        path="share1"  
        mountpoint="/media/%(USER)"
```

```

        options="user=%(USER),cuid=%(USER),sec=krb5i,file_mode=0770,dir_mode=0770"
/>

<!--
<luserconf name=".pam_mount.conf.xml" />
-->

<!-- Note that commenting out mntoptions will give you the defaults.
      You will need to explicitly initialize it with the empty string
      to reset the defaults to nothing. -->
<mntoptions allow="nosuid,nodev,loop,encryption,fsck,nonempty,allow_root,allow_other" />
<!--
<mntoptions deny="suid,dev" />
<mntoptions allow="" />
<mntoptions deny="" />
-->
<mntoptions require="nosuid,nodev" />

<logout wait="50000" hup="1" term="1" kill="1" />
<!-- <logout wait="0" hup="no" term="no" kill="no" /> -->
<!-- pam_mount parameters: Volume-related -->
<mkmountpoint enable="1" remove="true" />
</pam_mount>

```



/media/username. , . mountpoint="/home/%(USER)/share1" /share1/ . Astra Linux Special Edition , ,
PAM-, , pam_mount . :

1. pam_mount /etc/pam.d/common-session;
2. /etc/pam.d/login /etc/pam.d/fly-dm Astra Linux:

FreeIPA ():



session required pam_parsec_mac.so
session optional pam_mount.so

ALD ():



session required pam_parsec_mac.so
session required pam_ald.so
session optional pam_mount.so

(, samba home):

```

...
<volume
    fstype="cifs"
    server="ipa0.ipadomain.ru"
    path="% (USER)"
    mountpoint="/home/%(USER)"
    options="user=%(USER),cuid=%(USER),sec=krb5i,file_mode=0770,dir_mode=0770"
/>
...

```



Kerberos sec=krb5i (,) sec=krb5. **Kerberos** .



cuid=%(USER), .

mountpoint , : /media/ald_share. :





```
path="share" mountpoint="/media/ald_share" options="user=%(USER),rw,setuids,perm,soft,sec=krb5i,cuid=%(USERID),file_mode=0770,dir_mode=0770,iocharset=utf8,vers=1.0" />
```



logout . . .

mkmountpoint .

cifsmount , .

volume .

pam_mount

[homes], /home/<_> . pam_mount:

/etc/security/pam_mount.conf.xml

```
<?xml version="1.0" encoding="utf-8" ?>
<!DOCTYPE pam_mount SYSTEM "pam_mount.conf.xml.dtd">
<!--
    See pam_mount.conf(5) for a description.
-->

<pam_mount>
  <!-- debug should come before everything else,
        since this file is still processed in a single pass
        from top-to-bottom -->
  <debug enable="1" />

  <!-- Volume definitions -->
  <!-- homes -->
  <cifsmount>mount.cifs //%(SERVER)/%(USER) %(MNTPT) -o %(OPTIONS) </cifsmount>
  <!-- pam_mount parameters: General tunables -->
  <!-- , -->
  <volume
    fstype="cifs"
    server="ipa0.ipadomain.ru"
    path="%(USER)"
    mountpoint="/home/%(USER)"
    options="rw,user=%(USER),gid=%(USER),uid=%(USER),cuid=%(USER),sec=krb5i,file_mode=0770,
dir_mode=0770"
  />
  <!--
    <userconf name=".pam_mount.conf.xml" />
  -->

  <!-- Note that commenting out mntoptions will give you the defaults.
        You will need to explicitly initialize it with the empty string
        to reset the defaults to nothing. -->
  <mntoptions allow="nosuid,nodev,loop,encryption,fsck,nonempty,allow_root,allow_other" />
  <!--
  <mntoptions deny="suid,dev" />
  <mntoptions allow="*" />
  <mntoptions deny="*" />
  -->
  <mntoptions require="nosuid,nodev" />

  <logout wait="50000" hup="1" term="1" kill="1" />
  <!-- <logout wait="0" hup="no" term="no" kill="no" /> -->
  <!-- pam_mount parameters: Volume-related -->
  <mkmountpoint enable="1" remove="true" />
</pam_mount>
```



SAMBA AD winbind - user=%(DOMAIN_USER).

luserconf

pam_mount . , luserconf /etc/security/pam_mount.conf.xml pam_mount. :

```
luserconf name="<_>"
```

:

```
<luserconf name=".pam_mount.conf.xml" />
```

. , . , . , . , . , . , . , luserconf.

:

- mntoptions allow - , :

```
<mntoptions allow="user,cuid,vers,sec,nosuid,nodev,loop,encryption,fsck,nonempty,allow_root,allow_other" />
```

nosuid nodev, , ;

- mntoptions deny - . ;
- mntoptions require - . nosuid nodev, , ;

DFS

Distributed File System (DFS) Microsoft Windows . DFS, samba, cifs.

DFS keyutils:

```
sudo apt install keyutils
```

DFS (,), linux_5.4.0-110.astra35+ci1 linux-5.10_5.10.0-1057.astra6+ci7.

DFS , :

:

```
mount -t cifs //server1.active_directory.test/dfs1 ~/mnt -o cuid=user1,sec=krb5
```

:

```
mount -t cifs //active_directory.test/dfs1 ~/mnt -o cuid=user1,sec=krb5
```

DFS Kerberos :

1. . — . : SETSPN:

```
SETSPN -s cifs/<_> <_>
```

:

```
SETSPN -s cifs/ad12.loc w12
```

2. "-t" /etc/request-key.d/cifs.spnego.conf:



, "-t" , DNS- (DNS-), .

```
create cifs.spnego * * /usr/sbin/cifs.upcall -t %k
```

, DFS , samba, CIFS, .

pam_mount, :

reenter password for pam_mount



pam_mount, , .

/etc/pam.d/common-session :

session optional pam_mount.so

:

session optional pam_mount.so disable_interactive